



Product Features

The GF (General Filtration) GFS series single cartridge filter housings are constructed of all stainless steel and are suitable for a wide variety of commercial and industrial applications. GFS housings accept a single double open end (DOE) cartridge, and a machined knife edge seal ensures zero bypass. All sump seals are spring loaded to accept various cartridge lengths. GFS housings are available in 5 convenient lengths, to take cartridges from 4" to 40". All models come complete with a mounting bracket and wrench.

Advantages

- 304 stainless steel construction
- Maximum 300 psi @ 200°F
- In-line threaded connections
- Available in 4", 5", 10", 20", 30", and 40" nominal lengths
- Closure ring allows for quick and easy change out
- EPDM seals standard

Standard Connections

4" & 5" model—1/4" FNPT
 10" model—3/4" FNPT
 20" model—3/4" FNPT
 30" model—1" FNPT
 40" model—1" FNPT

GFS Ordering Information			EX: GFS20-3/4		Max Flow	
Model	Cartridge Length (inches)	Connection Size (inches)	Model	Max Flow		
GFS	4 (3.75")	-1/4"	GFS4	2 GPM		
	5 (4.875")	-1/2"	GFS5	3 GPM		
	10 (10")	-3/4"	GFS10	5 GPM		
	20 (20")	-1"	GFS20	10 GPM		
	30 (30")		GFS30	15 GPM		
	40 (40")		GFS40	20 GPM		

Parts List

- | | |
|--------------------|-----------------------|
| 01 - Cap | 09 - Inlet Port |
| 02 - Retainer Ring | 10 - Mounting Bracket |
| 03 - O-Ring (2) | 11 - Wrench |
| 04 - Shell | 12 - Hexagon Screw |
| 05 - Pedestal | |
| 06 - Petcock Drain | |
| 07 - Spring | |
| 08 - O-Ring | |

