



Product Features

- Micron ratings from 1 to 200
- Graded pore structure enhances dirt holding capacity and filtration efficiency
- Broad chemical compatibility allows for use in many applications
- Rigid construction makes GFP cartridges ideal for high viscosity applications
- High temperature resistance
- GFP50U30 custom cartridge fits in pump seal 1A1 filter housings

Product Specifications

- Media: Polyester and acrylic fibers with phenolic resin encapsulation
- Outside Diameter: 2.56" (65 mm)
- Inside Diameter: 1.06" (27mm)

Operating Parameters:

- Maximum Differential Pressure: 90 psid at 150°F (65°C)
- Maximum Operating Temperature: 250°F (121°C)
- Recommended Change-Out Pressure: 35 psid (2.4 bar)

GFP NOMENCLATURE

Filter Type	Retention Rating (microns)	Nominal Length (inches)
GFP	1	U30 (3-3/4")
	5	-4.75 (4-3/4")
	10	-9 (9-3/4")
	25	-10 (10")
	50	-19 (19-1/2")
	75	-20 (20")
	100	-29 (29-1/4")
	125	-30 (30")
	150	-39 (39")
	200	-40 (40")

CANADA WEST

3247 Roper Road NW
 Edmonton, AB T6P 0G1
 1-877-456-5760
saleswc@vytal.ca
www.vytal.ca

CANADA EAST

441 Applewood Crescent
 Concord, ON L4K 4J3
 1-888-233-1969
salesec@vytal.ca
www.vytal.ca

USA

345 E Tulare Ave
 Visalia, CA 93277
 1-424-222-7619
saleswusa@vytalusa.com
www.vytalusa.com